

CERTIFICATE OF CONFORMANCE

Beaded Porch Panel

MATERIAL SPECIFICATIONS

All products meet or exceed the Standard Specifications for Rigid PVC Soffit (ASTM D-4477) and its referenced documents. Where not defined in ASTM D-4477, products also meet Norandex Stringent Quality Control Standards.

PHYSICAL DATA

Panel Thickness: .040" (+/- .001")

Color: Uniformity is spectrophotometrically controlled.

Texture: Embossed with a low gloss brushed pattern.

Lock: Optically measured and controlled.

Gloss: Uniform low gloss maintained with a 75° glossmeter.

PRODUCT TEST DATA

Impact Resistance Mean Failure Energy:	> 45 in. lb.
Length:	Within-1/4" specification
Warp/Camber:	<1/8"
Coefficient of Linear Expansion (in/in/°F)	4.5x10 ⁻⁵

FIRE RESISTANCE

All siding, soffit, and accessories distributed by Norandex have a Class A flame spread classification per 2018 International Residential Code (IRC) and International Building Code (IBC).

ASTM E84:

Flame Spread Index: ≤20

Fuel Contribution: 0

ASTM D1929:

Self-Ignition Temperature: 860°F

ASTM D635:

Classified: CC1 **

** Tested specimens did not burn at 25 mm mark. Material was shown to be self-extinguishing. Therefore no average time of burning or average extent of burning can be calculated. For more information obtain a brochure on the fire properties of siding by contacting the Vinyl Siding Institute at www.vinylsiding.org

Profiles

Triple 2.6"

Solid or Center Vent

8" exposure

12' long

18 pieces/carton

1.44 squares/carton

COLORS (5)

- White
- Linen
- Champagne
- Wheat
- Sierra *

* Premium Colors featuring ColorHold® capping resins, a UV-Stable acrylic polymer