

NORANDEX HOUSEWRAP

will assure you are protecting your customer's home with a superior weather resistant barrier. Just one small way Norandex is putting your needs first.

Norandex Housewrap can be imprinted with business logo for maximum advertising exposure!!!



Housewrap is the "best practice" for protecting a home from wind and water while allowing it to breathe. Norandex makes it easy!

- Stronger than ever, our wrap can be installed with staples. No need for expensive cap nails
- Perm rating is appropriate for all climates
- Not affected by surfactants, such as soaps, cleaning agents, detergents
- Can be used under all types of products (e.g. vinyl siding, stucco, wood, steel, brick, stone and fiber cement)
- Features 9-month protection from ultraviolet degradation
- Lightweight and easy to cut
- Translucent so you can see through the wrap where to staple or nail
- Standard Norandex product is shipped within 5 days or less (NOT applicable to custom imprint orders)

- Micro-perforated to allow waterborne vapor to permeate out through the wrap and into the atmosphere
- Improves efficiency of wall insulation and seals cracks and seams in walls to reduce drafts for a more comfortable home
- Woven, polypropylene wrap is both tough and tear resistant
- Will not support mold growth
- Meets or exceeds standards for all code approvals
- Easy to order
- Custom imprinting program available with customer logo (one pallet minimum)
- Custom imprint orders will arrive within 14 days of receipt of order



NORANDEX HOUSEWRAP SPECIFICATIONS

QUALITY HOUSEWRAP	Product Specification	Test Method
Composition	Woven Polypropylene	
Weight Per Roll	11.8 lbs./MSF	
Thickness	5.5 mils	
Tensile Strength		ASTM D-882
Machine Direction	45.17	
Cross Direction	50.77	
Tear Strength		ASTM D-5034
Machine Direction	34.13	
Cross Direction	36.53	
Water Resistance	Pass	ASTM D-1709
MVTR/Perms	8 Perms	ASTM E-96
Fire Rating	Class A	ASTM E-94

Norandex Housewrap meets all national code requirements and can be used under all types of siding and masonry cladding materials. (Vinyl siding, stucco, wood, steel, brick, stone and fiber cement).

Meets the latest ICC Code requirements for water resistive barrier as well as new air barrier requirement with an air leakage rate of less than 0.02 L/S/m2 per ASTM 2178-03 in accordance with ICC AS-38.

Roll Size	Rolls per Pallet	
9 ft x 100 ft	50	
9 ft x 150 ft	45	
9 ft x 195 ft	40	
10 ft x 100 ft	50	
10 ft x 150 ft	45	
10 ft x 195 ft	40	
4.5 ft x 100 ft	100	



SEAMING TAPE Order in case qty (16 tape rolls/case) size: 3" x 165 feet

Freight prepaid on tape when ordered with a pallet of housewrap

Custom Imprinting Available!

Put your name right in the center of every wall you cover with our custom-imprinting program. Order your personalized house wrap one pallet at a time with no plate charges or additional printing fees. Order will arrive within 14 days of factory receipt of order.

One Pallet Minimum Quantity:

Additional Charge: None

Plate Charge: None (Up to 500

square inches max)

1 or 2 colors Logo: Standard colors at

no additional charge

PMS 186

PMS 202

BLUE PMS 492

PMS 485

YELLOW PANTONE C

YELLOW PMS 141

PURPLE PMS 274

BLUE PMS 280

PMS 287

GREEN PMS 357

GREEN PMS 342

GREEN PMS 382

> **BROWN** PMS 4635

> PMS 464

BLACK

GRAY PMS 425

Standard Colors Available

(Customization N/A on 3' x 150')